

Description

Self adhesive material for plotter. Polymeric gloss finish vinyls with high flexibility and conformability to curved surfaces, suitable for 5 years indoor/outdoor use. 52 colours available.

Printable in solvent and UV screenprinting.
Permanent acrylic with excellent water resistance.

For medium to long term indoor & outdoor signs.

Flammability DIN 752000: self-extinguishing resistance against chemicals and solvents DIN 51958.

Available in 610mm and 1260 mm.

Technical Data**Face Material**

Type	Special calendered PVC
Colour & Finish	52 available colours
Weight	107g/m ²
Thickness	75μ

Adhesive

Reference	Reference AP 900
Type	Acrylic permanent
Minimum Application Temperature	+10°C
Service Temperature	-30C/+80C
Shear	Very High
Tack GTM9	6N/inch ²
FinAdh FTM2	9N/inch

Release Backing

Type	1 side clay-coat
Colour & Finish	White
Weight	135g/m ²
Thickness	150μ

Technical Data (continued)**Characteristics**

Chemical Resistance:	Detergent	No effect (24 Hrs)
	Gasoline	No effect (1 Hrs)
	SAE20 Motoroil	No effect (24 Hrs)
	10% HCl	No effect (10 min)
	10% NH ₄ OH	No effect (10 min)

Processing**Storage:**

The material must be stored at a temperature of 22°C +/- 2°C and 50% +/- 5% of Relative Humidity.

Do not expose to direct sun light.

The area must be dry and clean. Please keep the material in the original packaging when not used in order to protect it from dust and contaminations.