Monomeric Gloss Overlaminate

Monomeric digital laminating vinyl

Description
The clear overlaminating film is design to be used with the DeTape range of monomeric digital print media.

Available from stock in 760mm, 1370mm and 1550mm widths.

Technical Data

General

Face Film	Monomeric vinyl - clear
Thickness	70 µ ±10% ISO 534-80
Weight	93 g/m² ±10% ISO-536
Release Liner	One side siliconised Glassine

Adhesive

Adhesive Type	Acrylic permanent water based adhesive.	
Temperature:	Application Temperature:	+10°C
	Service Temperature Range:	-30 °C up to +120 °C
Shear	Medium	
Tack	Medium N/inch²	
Final Adhesion	High N/inch	

Release Liner

Colour	White
Type	One side siliconised Glassine
Weight	62 g/m² ±10%
Thickness	55 µ ±10%

Storage

Before application the films can be stored for minimum 24 months from date of production.

The film must be stored at room temperature (20-24 °C) and a relative humidity of the air of 50% (+/- 5%). To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed `hanging´ racks. Do not expose to direct sunlight or heat sources.

All technical data and advice is based on the manufacturer's experience and measured testing that we believe to be reliable.
It remains the customer's responsibility to test our products suitability for the purpose intended.