Gloss White With Grey Adhesive

Monomeric digital print vinyl

Description

This monomeric self adhesive film is designed for digital printing with solvent, eco solvent, latex and UV printers.

This film is monomeric so is suitable for flat surfaces or a minimal curved surface.

The adhesive is grey to give blockout properties.

Available from stock in 760mm, 1370mm and 1550mm widths.

General

Face Film	Monomeric vinyl
Thickness	80 µ ±10%
Adhesive	Acrylic permanent water based adhesive - grey
Release Liner	Silicone clay coated Kraft
Grade	Suitable for interior or exterior use. Exterior life - 3-5 years.

Adhesive

Grey permanent water based acrylic adhesive. Designed for application to glass, acrylonitrile butadiene styrene (ABS), polystyrene (PS), polyvinyl chloride (PVC) and painted metal such as vehicles. Not suitable for low energy substrates such as polyethylene and polypropylene.

Temperature:	Application Temperature:	+10°C
	Service Temperature Range:	-30 °C up to +120 °C
Shear	Medium	
Tack	Medium N/inch²	
Final Adhesion	High N/inch	

Release Liner

Colour	White
Type	One side siliconised clay coated Kraft
Weight	135 g/m² ±10%
Thickness	145 µ ±10%

Storage

Before application the films can be stored for minimum 24 months from date of production.

The film must be stored at room temperature (20-24 °C) and a relative humidity of the air of 50% (+/- 5%). To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed `hanging´ racks. Do not expose to direct sunlight or heat sources.

All technical data and advice is based on the manufacturer's experience and measured testing that we believe to be reliable.
It remains the customer's responsibility to test our products suitability for the purpose intended.