


General

Mirror your graphic in your cutting software and cut on the matt / reverse side. Cut the garment film using the same pressure as standard sign vinyl. Cool Flex, Artflex, Prem Flock and Pro Flock may require a slightly higher pressure setting as these films are thicker.

You can press using a heat press using the settings detailed below or by using a domestic iron on (or just below) the hottest cotton setting with no steam and allowing a extra few seconds of application time.







General Purpose Coloured Continued



Solvent-free, water-based polyurethane garment vinyl with a paper carrier liner. Suitable for Polyester, Cotton and Nylon. Medium pressure. For Nylon press at 150°C / 10 seconds, and peel carrier cold. Press again at 150°C for 30 seconds. Nylon max wash 40°C



Flock **Pro-Flock** Tumble Cool 60°C 170°C 10-15 Peel Dry Clean sec Suitable for Polyester and Cotton Prem-Flock Hot Tumble Dry 15 sec 60°C 160°C Peel Drv Clean Suitable for Polyester and Cotton **Metallics & Sparkles Cool Flex** Cool Tumble Dry 60°C 15 sec 160°C Peel Clean Suitable for Polyester and Cotton




Pearlescent effect garment vinyl suitable for Polyester and Cotton. Medium pressure.

Specialist Applications

+ 10

150°C





Suitable for nylon garments. Apply for 20 seconds, remove backing and repress for a further 10 seconds

Peel

Clean

Dry





Perforated PU garment vinyl suitable for Polyester and Cotton. Medium pressure.