

Inkjet Printable For Light Garments



Artwork

Mirror your artwork before you print.

Printing

Print onto the blank side of the film. If your printer has an option for Photo Quality or Photo Paper, use that setting.

Application

Remove excess material but leave a narrow margin around the printed image.

Pre heat garment for 5 seconds

Place image face down cover with silicon paper.

Press at 175°C for 15 seconds. Peel back liner when still hot.

Washing

Turn inside out before washing/ironing

Do not dry clean

Do not use fabric softener

Do not tumble

Do not use bleach

Colour Activ Inkjet Printable For Light Garments



Artwork

Mirror your artwork before you print.

Printing

Set printer to plain paper and fine or photo quality. Allow the ink to dry for 10 minutes prior to application.

Application

Remove excess material prior to application. Pre heat garment for 4 seconds to remove any residual moisture.

Press at 175°C for 15 seconds. Use a heavy pressure.

After pressing pull each side of the t-shirt, this will expose a corner of the paper so it can be removed easily.

Remove paper immediately after pressing.

After the paper has been removed, you can gently stretch the t-shirt in both directions to give the transfer a softer feel.

Washing

Machine washable up to 40°C

Do not use bleach or harsh washing detergents.

Continued On Page 2

Go to www.mdpsupplies.com or come instore to see our full range of supplies for signmakers and garment printers



NEENAH PERFORMANCE MATERIALS

Neenah Jet Pro Soft Stretch For Light Garments

NEENAH

Jet Pro SS

light inkjet

Instructions for Inkjet Printers

- 1 Print the image in mirrored format.
- 2 Trim away the unprinted areas of the transfer.
- 3 Set heat press to 190°C - medium / heavy pressure (30 psi/3 to 5 bar).
- 4 Place the sheet on top of the light coloured garment with the image side down.
- 5 Press for 30 seconds.
- 6 Peel back sheet whilst still hot, in a smooth, even motion.
- 7 For greatest softness, quickly stretch the fabric in all directions while still hot.

Inkjet Printable For Dark Garments



160°C



10 sec



80°C



Tumble Dry



Dry Clean

Artwork

Do not mirror your artwork.

Printing

Print onto the smooth matt side of the film. If your printer has an option for Photo use that setting, alternatively just select plain paper.

Application

Remove excess material prior to application. Peel back print off backing and cover with silicone paper.

Press at 160°C for 10 seconds. Use a light to medium pressure.

If applying to dyed polyester (some sportswear) press at 155°C for 10 seconds

Washing

Machine washable up to 80°C

Do not use bleach or harsh washing detergents.

Continued On Page 3

Go to www.mdpsupplies.com or come instore to see our full range of supplies for signmakers and garment printers



Colour Activ Inkjet Printable For Dark Garmentscolour **Activ****160°C****20 sec****Cool****Tumble Dry****Dry Clean****Artwork**

Do not mirror your artwork.

Printing

Print selected image on the blank side of the transfer paper. Allow the ink to dry for 10 minutes prior to application.

Application

Remove excess material prior to application. Peel back print off backing and cover with silicone paper.

Press at 160°C for 20 seconds. Use a medium pressure.

Remove silicone paper cold

Washing

Machine washable in a cool wash

Do not use bleach or harsh washing detergents.

NEENAH PERFORMANCE MATERIALS**Neenah 3G Jet Opaque For Dark Garments****NEENAH**
3G Jet Opaque
dark inkjet**Instructions for Inkjet Printers**

- 1 Print the image onto the coated side of the sheet.
- 2 Bend a corner to remove the backing paper from the printed image.
- 3 Set heat press to 177°C - medium / heavy pressure (30-45 psi / 2 to 3 bar).
- 4 Place the sheet on top of the dark coloured garment with the image facing up.
- 5 Cover image with one sheet of parchment / silicone paper.
- 6 Press for 30 seconds.
- 7 Once cold, peel back sheet in a smooth, even motion.

Go to www.mdpsupplies.com or come instore to see our full range of supplies for signmakers and garment printers